

AVIFIX High Tack

1. Identification of the substance/preparation and of the company/undertaking

1.1 Identification of the substance or preparation:

Product name : AVIFIX High Tack

1.2 Use of the substance or the preparation:

Sealant

1.3 Company/undertaking identification:

SODAL N.V.
Everdongenlaan 18-20
B-2300 Turnhout
Tel: +32 14 42 42 31
Fax: +32 14 44 39 71
e-mail address: msds@soudal.com

1.4 Emergency telephone:

+32 14 58 45 45 (24/24 h)
Information centre on dangerous goods (BIG)
Technische Schoolstraat 43 A, B-2440 Geel, Belgium

2. Composition/information on ingredients

Hazardous ingredients	CAS No. EINECS/ELINCS No.	Conc. in %	Hazard symbol	Risks (R-phrases)
bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate	52829-07-9 258-207-9	0.1 - 1.0	Xi;N	36-51/53 (1)
trimethoxyvinylsilane	2768-02-7 220-449-8	1 - 20	Xn	10-20 (1)
dibutylbis(pentane-2,4-dionato- O,O')tin	22673-19-4 245-152-0	0.1 - 1.0	Xn;N	36/38-48/22-51/53 (1)

(1) For R-phrases in full: see heading 16

3. Hazards identification

- No hazard classification according to Directive 67/548/EEC and 1999/45/EC

4. First aid measures

- 4.1 Eye contact:**
- Rinse immediately with plenty of water
 - Seek medical advice
- 4.2 Skin contact:**
- Rinse immediately with plenty of water
 - If irritation persists: seek medical advice
- 4.3 After inhalation:**
- Remove the victim into fresh air
 - Seek medical advice
- 4.4 After ingestion:**
- Never give water to an unconscious person
 - Do not induce vomiting
 - Seek medical advice

5. Fire-fighting measures

- 5.1 Suitable extinguishing media:**
- Polyvalent foam
 - Dry chemical powder
 - Carbon dioxide
- 5.2 Unsuitable extinguishing media:**
- None
- 5.3 Special exposure hazards:**
- Not easily combustible
 - On burning: release of carbon monoxide and carbon dioxide
- 5.4 Instructions:**
- No specific firefighting instructions required
- 5.5 Special protective equipment for firefighters:**
- Heat/fire exposure: compressed air/oxygen apparatus

6. Accidental release measures

- 6.1 Personal protection/precautions:** See heading 8.2
- 6.2 Environmental precautions:**
- Use appropriate containment to avoid environmental contamination
 - See heading 13
- 6.3 Methods of cleaning up:**
- Cover the solid spill with sand/kieselguhr
 - Scoop solid spill into closing containers
 - Clean contaminated surfaces with an excess of water

AVIFIX High Tack

7. Handling and storage

7.1 Handling:

- Observe normal hygiene standards

7.2 Storage:

- Keep container tightly closed
- Store in a dry area

Storage temperature : room temperature
Quantity limit : N.D. kg
Storage life : 365 days
Materials for packaging :
- suitable : plastics

7.3 Specific uses:

- See information supplied by the manufacturer

8. Exposure controls/Personal protection

8.1 Exposure limit values:

TLV-TWA : not listed
TLV-STEL : not listed
TLV-Ceiling : not listed

WEL-LTEL : not listed
WEL-STEL : not listed

TRGS 900 : not listed

MAK : not listed

GWBNI-TGG 8 h : not listed
GWKNI-TGG 15 min. : not listed
Ceiling : not listed

VME-8 h : not listed
VLE-15 min. : not listed

GWBB-8 h : not listed
GWK-15 min. : not listed
Momentary value : not listed

EC : not listed
EC-STEL : not listed

AVIFIX High Tack

8.2 Exposure controls:

8.2.1 Occupational exposure controls:

- Use only in well ventilated area

8.2.2 Environmental exposure controls: see heading 13

8.3 Personal protection:

8.3.1 respiratory protection:

- In case of insufficient ventilation: respiratory protection with filter type A

8.3.2 hand protection:

- Gloves

8.3.3 eye protection:

- Safety glasses

8.3.4 skin protection:

- Suitable protective clothing

9. Physical and chemical properties

9.1 General information:

Appearance (at 20°C)	: Paste
Odour	: Almost odourless
Colour	: Variable in colour

9.2 Important health, safety and environmental information:

pH value	: N.D.	
Boiling point/boiling range	: N.D.	°C
Flashpoint	: N.D.	°C
Explosion limits	: N.D.	Vol%
Vapour pressure (at 20°C)	: N.D.	hPa
Vapour pressure (at 50°C)	: N.D.	hPa
Relative density (at 20°C)	: 1.7	
Water solubility	: Insoluble	
Soluble in	: Organic solvents	
Relative vapour density	: N.D.	
Viscosity (at 20°C)	: N.D.	Pa.s
Partition coefficient n-octanol/water	: N.D.	
Evaporation rate		
ratio to butyl acetate	: N.D.	
ratio to ether	: N.D.	

9.3 Other information:

Melting point/melting range	: N.D.	°C
Auto-ignition point	: N.D.	°C
Saturation concentration	: N.D.	g/m ³

10. Stability and reactivity

10.1 Conditions to avoid/reactivity:

- Stable under normal conditions

10.2 Materials to avoid:

- None

10.3 Hazardous decomposition products:

- On burning: release of carbon monoxide, carbon dioxide and formation of small quantities of nitrous vapours

11. Toxicological information

11.1 Acute toxicity:

bis(2,2,6,6-TETRAMETHYL-4-PIPERIDYL)SEBACATE:

LD50 oral rat	: 3700	mg/kg
LD50 dermal rat	: > 2000	mg/kg
LD50 dermal rabbit	: > 3100	mg/kg
LC50 inhalation rat	: N.D.	mg/l/4 h
LC50 inhalation rat	: N.D.	ppm/4 h

TRIMETHOXYVINYL-SILANE:

LD50 oral rat	: 7120	mg/kg
LD50 dermal rat	: N.D.	mg/kg
LD50 dermal rabbit	: 3434	mg/kg
LC50 inhalation rat	: 16	mg/l/4 h
LC50 inhalation rat	: 2714	ppm/4 h

11.2 Chronic toxicity:

EC carc. cat.	: not listed
EC muta. cat.	: not listed
EC repr. cat.	: not listed

Carcinogenicity (TLV)	: not listed
Carcinogenicity (MAC)	: not listed
Carcinogenicity (VME)	: not listed
Carcinogenicity (GWBB)	: not listed

Carcinogenicity (MAK)	: not listed
Mutagenicity (MAK)	: not listed
Teratogenicity (MAK)	: not listed

IARC classification	: not listed
---------------------	--------------

11.3 Routes of exposure: ingestion, inhalation, eye and skin

11.4 Acute effects/symptoms:

- Unlikely to cause harmful effects

11.5 Chronic effects:

- Unlikely to cause harmful effects

12. Ecological information

12.1 Ecotoxicity:

bis(2,2,6,6-TETRAMETHYL-4-PIPERIDYL)SEBACATE:

- LC50 (96 h) : 4.4 mg/l (BRACHYDANIO RERIO)
- EC50 (24 h) : 17 mg/l (DAPHNIA SP.)
- EC50 (72 h) : 1.9 mg/l (SCENEDESMUS SUBSPICATUS)

TRIMETHOXYVINYL-SILANE:

- LC50 (96 h) : >= 100 mg/l (BRACHYDANIO RERIO)
- EC50 (48 h) : 168.7 mg/l (DAPHNIA MAGNA)

12.2 Mobility:

- Volatile organic compounds (VOC): 2 %
- Volatile organic compounds (VOC): 34 g/l
- Insoluble in water
- Substance sinks in water
- For other physicochemical properties see section 9

12.3 Persistence and degradability:

- biodegradation BOD₅ : N.D. % ThOD
- water : No data available
- soil : T ½ N.D. days

12.4 Bioaccumulative potential:

- log P_{ow} : N.D.
- BCF : N.D.

12.5 Other adverse effects:

- W GK : 1 (Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 17 May 1999)
- Effect on the ozone layer : Not dangerous for the ozone layer (1999/45/EC)
- Greenhouse effect : No data available
- Effect on waste water purification : No data available

13. Disposal considerations

13.1 Provisions relating to waste:

- Waste material code (75/442/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 08 04 10 (waste adhesives and sealants other than those mentioned in 08 04 09)

13.2 Disposal methods:

- No data available

13.3 Packaging:

- Waste material code packaging (75/442/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 15 01 02 (plastic packaging)

14. Transport information

- 14.1 Classification of the substance in compliance with UN Recommendations
- UN number : -
 - CLASS : NOT SUBJECT
 - SUB RISKS :
 - PACKING :
 - PROPER SHIPPING NAME :
- 14.2 ADR (transport by road)
- CLASS : NOT SUBJECT
 - PACKING :
 - DANGER LABEL TANKS :
 - DANGER LABEL PACKAGES :
- 14.3 RID (transport by rail)
- CLASS : NOT SUBJECT
 - PACKING :
 - DANGER LABEL TANKS :
 - DANGER LABEL PACKAGES :
- 14.4 ADNR (transport by inland waterways)
- CLASS : NOT SUBJECT
 - PACKING :
 - DANGER LABEL TANKS :
 - DANGER LABEL PACKAGES :
- 14.5 IMDG (maritime transport)
- CLASS : NOT SUBJECT
 - SUB RISKS :
 - PACKING :
 - MFAG :
 - EMS :
 - MARINE POLLUTANT :
- 14.6 ICAO (air transport)
- CLASS : NOT SUBJECT
 - SUB RISKS :
 - PACKING :
 - PACKING INSTRUCTIONS PASSENGER AIRCRAFT :
 - PACKING INSTRUCTIONS CARGO AIRCRAFT :
- 14.7 Special precautions in connection with transport : Not restricted for any mode of international transport

15. Regulatory information

Labelling in accordance with EC directives 67/548/EEC and 1999/45/EC

LABELLING NOT REQUIRED ACCORDING TO AVAILABLE INFORMATION

16. Other information

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

N.A. = NOT APPLICABLE
N.D. = NOT DETERMINED
***** = INTERNAL CLASSIFICATION

Exposure limits:

TLV : Threshold Limit Value - ACGIH USA
WEL : Workplace Exposure Limits - United Kingdom
TRGS 900 : Technische Regel für Gefahrstoffe 900 (Arbeitsplatzgrenzwerte) - Germany
MAK : Maximale Arbeitsplatzkonzentrationen - Germany
GWBNL : Grenswaarde voor blootstelling - The Netherlands
GWKNL : Grenswaarde korte duur - The Netherlands
VME : Valeurs limites de Moyenne d'Exposition - France
VLE : Valeurs Limites d'Exposition à court terme - France
GWBB : Grenswaarde beroepmatige blootstelling - Belgium
GWK : Grenswaarde kortstondige blootstelling - Belgium
EC : Indicative occupational exposure limit values

Indicative occupational exposure limit values - directive 2000/39/EC

I : Inhalable fraction = **T** : Total dust = **E** : Einatembarer Aerosolanteil
R : Respirable fraction = **A** : Alveolengängiger Aerosolanteil/Alveolar dust
C : Ceiling limit

a: aerosol		r: rook/Rauch	(fume)
d: damp	(vapour)	st: stof/Staub	(dust)
du: dust		ve: vezel	(fibre)
fa: Faser	(fibre)	va: vapour	
fi: fibre		om: oil mist	
fu: fume		on: olienevel/Ölnebel	(oil mist)
p: poussière	(dust)	part: particles	

Chronic toxicity:

K : List of the carcinogenic substances and processes - The Netherlands 2002

Full text of any R-phrases referred to under heading 2:

R10 : Flammable
R20 : Harmful by inhalation
R36 : Irritating to eyes
R36/38 : Irritating to eyes and skin
48/22 : Harmful: danger of serious damage to health by prolonged exposure if swallowed
R51/53 : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment